



Bride droite GTR Titan

GTR Titán straight connector

REVISION: **00**Fam.: **GTR (G/N)**Page **1/1**

DECRIE SERIL ZI de la tuilliere 01700 MIRIBEL FRANCE · Tel: +33 (0)4 72 25 83 17·

DESCRIPTION

Connecteur droite en polyamide (PA6).
 Sans halogene, phosphore ni cadmium.
 Resistant aux chocs et à la propagation de la flamme.
 Pour la fixation de l'extremite des gaines larges sur des plans plats, remplies d'un nombre important de cables.
 En accord avec la norme EN 60204 (Sécurité des machines).
 Grande résistance à la traction et aux vibrations.
 Protection IP66 ou IP68 avec les joints ORJ et TTJ.
 Couleur: gris foncé ou noir.

DESCRIPTION

Straight connector manufactured from high-quality polyamide (PA6).
 Free of halogens, phosphorus and cadmium.
 Shock resistant and not flame propagator.
 For fixing the ends of flexible corrugated conduits with large number of cables to the cable entries on control panels in electrical installations fitted in accordance with standard EN 60204 (Safety of Machinery).
 Vibration proof.
 High tensile strength.
 IP66 protection. IP68 with ORJ O-rings and TTJ sealing washers
 Colours: dark grey and black

CARACTERISTIQUE DIMENSION / DIMENSIONAL CHARACTERISTICS

Reference / Reference		DN (*)	Ø int.	A	C	E	F	G	H	Poids / Weight g	sachet de / Packing u.
GRIS / GREY	NOIR / BLACK										
GTR-70G	GTR-70N	70	71,0	43	101	119	6,5	105	30°	109,0	5
GTR-95G	GTR-95N	95	98,0	43	130	146	6,5	132	30°	153,6	5

(*) DN = Diametre Nominal de la gaine / Nominal Diameter of the conduit to use
 Dimension en mm / Dimensions in mm

